CHIRCH DIALES I ALCH. 1191	Uni	ted	States	Patent	[19]
----------------------------	-----	-----	---------------	--------	------

Rollhaus et al.

3,597,538

3,892,915

4,042,777

4,344,069

4,381,502

4,502,038

4,360,892 11/1982

8/1971

7/1975

8/1977

8/1982

4/1983

2/1985

[11] Patent Number:

4,694,280

[45] Date of Patent:

Sep. 15, 1987

[54]	KEYBOAR	RD ENTRY SYSTEM	
[75]	Inventors:	Philip E. Rollhaus, Chicago, II Yukio Endo, Thornton, N.H.	l.;
[73]	Assignee:	Quixote Corporation, Chicago,	Ill.
[21]	Appl. No.:	856,644	
[22]	Filed:	Apr. 25, 1986	
	Relat	ted U.S. Application Data	
[63]	Continuation Pat. No. 4,6	n-in-part of Ser. No. 574,894, Jan. 30 38,306.	, 1984,
[51] [52]			65 E;
[58]		arch	65 E;
[56]		References Cited	
	U.S. F	PATENT DOCUMENTS	
	3,225,883 12/1 3,381,270 4/1	965 Ayres 340,	/365 S

0077658 4/1983 European Pat. Off. 340/365 R

Birenbaum 178/17.5

Budworth et al. 340/365 S

Bequaert et al. 340/365 R

Prame 340/365 S

Endfield 340/365 S

Prame 340/365 R

Lowenthal et al. 340/365 S

58-72493	11/1983	Japan	340/365	R
2076743	12/1981	United Kingdom	340/365	R

Primary Examiner—James L. Rowland
Assistant Examiner—T. Rittmaster

Attorney, Agent, or Firm—Willian Brinks Olds Hofer Gilson & Lione Ltd.

ABSTRACT

onson w zione zia

A keyboard entry system is disclosed which comprises a keyboard which includes a plurality of letter keys, one for each letter of a selected language. The entry system responds to conventional sequential activation of individual keys by providing output signals indicative of the respective individual letters associated with the activated keys to an application program such as a word processor or printer control program. The keyboard entry system also responds to chords of simultaneously activated multiple keys by using these chords to retrieve stored words from a dictionary. It is the stored words rather than the entered chords which are applied as inputs to the application program. This system allows an operator to use both conventional sequential key entry techniques and chorded entry techniques for rapid data entry. Chords are detected by comparing a stored constant with the elapsed time between a key release and the immediately preceding key depression of an overlapping key. The overlapping keys are characterized as a chord when the elapsed time is greater than the stored constant. A biofeedback mechanism alerts the operator of inadvertent chords.

22 Claims, 7 Drawing Figures

